










### BALANCE YOUR WORK LIFE

IN YOUR GARDEN

Achieve your work/life balance with the Xtend range of garden buildings from Forest Garden. These new buildings have everything you could wish for in a home office - contemporary looks, real energy efficiency, ease of construction and keen pricing, brought to you by the UK's largest manufacturer of timber garden products.



































The Xtend 2.5 with a single door and 4 opening window.

Overall size

250(h) x 254(w) x 290(d)cm

Footprint

253(w) x 250(d)cm

Ridge height

250cm

Eaves height

235cm

Internal size

206(h) x 217(w) x 215(d)cm





#### **Option 1**

Single door and full length fixed pane window to front, full length 1/4 opening side window.





The Xtend 2.5+ with a single door and ½ opening window.

Overall size

250(h) x 254(w) x 290(d)cm

Footprint

253(w) x 250(d)cm

Ridge height

250cm

Eaves height

235cm

Internal size

206(h) x 217(w) x 215(d)cm





#### Option 2

Single door and full length fixed pane window to front, full length 1/2 opening side window.





The Xtend 3.0 with a single door and ¼ opening window.

Overall size

250(h) x 298(w) x 290(d)cm

Footprint

297(w) x 250(d)cm

Ridge height

250cm

Eaves height

240cm

Internal size

206(h) x 261(w) x 215(d)cm

3.0





**Single door** and two full length fixed pane windows to front, full length **1/4 opening** side window.





The Xtend 3.0+ with double doors and two ½ opening windows.

Overall size

250(h) x 298(w) x 290(d)cm

Footprint

297(w) x 250(d)cm

Ridge height

250cm

Eaves height

240cm

Internal size

206(h) x 261(w) x 215(d)cm

3.0+



#### Option 2

Double doors and full length ½ opening window to front, full length ½ opening side window.





The Xtend 4.0 with a single door and ¼ opening window.

Overall size

250(h) x 405(w) x 342(d)cm

Footprint

403(w) x 304(d)cm

Ridge height

250cm

Eaves height

240cm

Internal size

206(h) x 367(w) x 268(d)cm





#### **Option 1**

**Single door** and two full length fixed pane windows to front, full length **1/4 opening** side window.





The Xtend 4.0+ with double doors and two ½ opening windows.

Overall size

250(h) x 405(w) x 342(d)cm

Footprint

403(w) x 304(d)cm

Ridge height

250cm

Eaves height

240cm

Internal size

206(h) x 367(w) x 268(d)cm





#### Option 2

Double doors and full length 1/2 opening window to front, full length 1/2 opening side window.






## STRUCTURAL INSULATED PANELS (SIPs)

The core structure of an Xtend building is made from SIPs panels - high performance material for building construction. The 21st century way to build.

- 97mm thick insulated walls consist of 75mm of polystyrene insulation sandwiched by two sheets of oriented strand board (OSB)
- Gives structure and insulation in one pre-assembled and cut-to-size panel



- Total wall thickness including SIPS panels, internal and external cladding and cavities is 177mm
- Roof is 11mm OSB + 100mm insulation + 11mm OSB = 122mm total

## EXTERNAL CLADDING

Pre-cut external timber cladding panels for quick and easy assembly.



- Cladding panels are simply positioned on the building and screwed into place
- Panels are made with 15mm thick premium interlocking tongue and groove boards mounted to framing battens




- Comes untreated and we recommend the application of any of the following:
- Sikkens Cetol HLS Plus
- Restol Wood Oil
- Timmersol ETS Double Protectant
- Osmo Country Colour
- Osmo Natural Oil Woodstain

#### INTERNAL CLADDING

Pre-cut interior MDF panels for quick and easy assembly for walls and ceiling.

- Pre-cut interior MDF panels for quick and easy assembly for walls and ceiling
- No measuring and cutting every panel
- Wall panels are mounted to 28mm thick battens creating a cavity perfect for routing electrical wiring
- Roof battens are 45mm thick to allow for recess roof lights



- Comes with primer applied can be painted in a colour of your choice using standard interior emulsion paint
- The panel design has a vertical beaded profile
- The floor is left unfinished for you to add your own choice of covering

#### ROOF COVERING

External roof covering is made from 1.2mm thick EPDM black rubber.



- It creates a maintenance free waterproof membrane
- Does not crack, split or rot
- Does not support moss or algae growth
- UV stable & environmentally friendly

- Safe and easy to install the system is laid with cold applied adhesives (supplied)
- One piece sheet means no joints and no leaks
- 50 years roof life expectancy
- Anthracite grey fascias included

#### WINDOWS & DOORS

#### Specification

Window material uPV

uPVC 5 chamber

Window colour

Anthracite grey externally with grained finish Smooth white internally

Window locking

Two double clasp, mushroom headed espagnolettes

**Door material** 

uPVC reinforced 5 chamber

Door colour

Anthracite grey externally with grained finish Smooth white internally

**Door locking** 

7 point multi-lock with ultion three star security barrel

Glazing

28mm, A rated, double glazed, safety glass










# ENERGY EFFICIENCY

- Highly efficient insulated walls roof and floor
- Double glazed windows
- Warm in Winter, cool in Summer
- Energy efficiency model rating of 78 (category C)\*
- Potential to increase to 82 (category B) with the addition of a photovoltaic solar panel
- \* based on lighting from 3 x 4 watt LED bulbs and heat from a high efficiency wall mounted heat pump.



#### Heating need per unit floor area





Model	Width	Depth	m²	kWh/m²a	Cost per kWh	kWh per annum	Cost per annum
Xtend 2	2.50	2.50	6.25	100	£0.15	625	£93.75
Xtend 3	3.00	3.50	10.5	100	£0.15	1050	£157.50
Xtend 4	4.00	3.00	12	100	£0.15	1200	£180.00















